

FLOS

Glo-Ball S1 (Halogen) - Specification Sheet by Jasper Morrison, 1998

| | |
|-----------------------------------|---|
| Mounting | Ceiling Pendant |
| Lamp (Bulb) Description | 1 x 100W T8 E26 Base Frosted Halogen (Included) |
| Canopy Dimension | Diameter 5.75" - 1.40" high |
| Environment | Indoor - Dry Location |
| Dimming | Phase-cut Dimming / Triac Type |
| Finish | Opal |
| Technical and Product Description | GLO-BALL S pendant lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Transparent, injection molded polycarbonate diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable. |

Electrical

| | |
|-----------|------|
| Voltage | 120 |
| IP Rating | IP20 |


Physical

| | |
|-----------------------|--------------|
| Cord Length (inches) | 106" - Clear |
| Construction Material | Glass |
| Weight | 6.3 lbs |



FU300561 Opal

Dimensional Image



Certifications



Lamping (Bulb)



100W T8 E26 Base Frosted Halogen

Lamping (Bulb)



LED018 PRO-T38LED 14W 120V E26 2700K
DIMM - 1800lm - CR180 Additional

Lamping (Bulb)



LED031 PRO-T38LED 14W 120V E26 3000K
Dimmable - 1800lm - CR180- Additional